INTRODUCING IMPROVED DRY CORE BITS

New redesigned barrel brings changes to the cooling holes and grooves for **added strength, speed and control of silica dust.** The segment has been improved with a new formula that increases speed without sacrificing life. Segment dimensions have been modified to maximize the welding surface which creates a stronger weld. **FOR MASONRY APPLICATION ONLY.**

ODZ30PR		OD30P	
Part Number	*Description*	*Part Number*	*Description*
ODZ30PR01011A2NC	1 X .110 X 5/8-11	OD30P01011A2NC	1 X .110 X 5/8-11
ODZ30PR01211A2NC	1 1/4 X .110 X 5/8-11	OD30P01211A2NC	1 1/4 X .110 X 5/8-11
ODZ30PR01511A2NC	1 1/2 X .110 X 5/8-11	OD30P01511A2NC	1 1/2 X .110 X 5/8-11
ODZ30PR01711A2NC	1 3/4 X .110 X 5/8-11	OD30P01711A2NC	1 3/4 X .110 X 5/8-11
ODZ30PR02012A2NC	2 X .125 X 5/8-11	OD30P02012A2NC	2 X .110 X 5/8-11
ODZ30PR02212A2NC	2 1/4 X .125 X 5/8-11	OD30P02212A2NC	2 1/4 X .110 X 5/8-11
ODZ30PR02512A2NC	2 1/2 X .125 X 5/8-11	OD30P02512A2NC	2 1/2 X .110 X 5/8-11
ODZ30PR03012A2NC	3 X .125 X 5/8-11	OD30P03012A2NC	3 X .110 X 5/8-11
ODZ30PR03512A2NC	3 1/2 X .125 X 5/8-11	OD30P03512A2NC	3 1/2 X .110 X 5/8-11
ODZ30PR04012A2NC	4 X .125 X 5/8-11	OD30P04012A2NC	4 X .125 X 5/8-11
ODZ30PR04212A2NC	4 1/4 X .125 X 5/8-11	OD30P04512A2NC	4 1/2 X .125 X 5/8-11
ODZ30PR04512A2NC	4 1/2 X .125 X 5/8-11	OD30P05012A2NC	5 X .125 X 5/8-11
ODZ30PR05012A2NC	5 X .125 X 5/8-11	OD30P06012A2NC	6 X .125 X 5/8-11
ODZ30PR06012A2NC	6 X .125 X 5/8-11		

GENERAL TOOL

gtdiamond.com